

TRICON OFFICE

The Tricon Office Module is a modified standard Tricon I equipped with a 110V single phase electrical system, pre-wired for telephone and CAT5 cabling. The office module can easily serve the needs of one to two personnel in a deployed environment.

The office is equipped with a commercial-grade environmental control unit for heating and cooling, which is shipped inside the Office Module and easily installed onsite.



CMCI produces a broad range of American-made and integrated, intermodal equipment that is unrivaled in quality and performance. Strategically located in Charleston, South Carolina, CMCI can service your requirements by land, sea and air.

cmci

Charleston Marine Containers, Inc.
A Gichner Systems Group Company

For information on how to order:

Charleston Marine Containers Inc.

2301 Noisette Blvd
Charleston, South Carolina
29405

Toll Free: 1-877-775-3795

Tel: (843) 747-3795

Fax: (843) 747-3798

info@cmci.com
www.cmci.com

DURABLE VERSATILE AFFORDABLE



Charleston Marine Containers, Inc.
A Gichner Systems Group Company

For information on how to order:

Charleston Marine Containers Inc.

2301 Noisette Blvd
Charleston, South Carolina
29405

Toll Free: 1-877-775-3795
Tel: (843) 747-3795
Fax: (843) 747-3798

info@cmci.com
www.cmci.com



GSA: GS-02F-0205N

TRICON OFFICE

Features include:

- All-steel monocoque construction
- Three-way forklift pockets
- Full-width access doors on one side of container
- Over 5.5 tons (12,000 pounds) payload capacity
- ISO tested and CSC approved by Lloyds for use in the 20' module configuration
- Over 9.6 cubic meters (346 cubic feet) of internal capacity
- Easily repaired (essentially same construction as a 20' steel container)
- 1 Year Warranty on Materials and Workmanship
- 5 to 20-Year Anti-Corrosion Warranty
- Standard 36-inch wide personnel door installed in the side with lockable hardware
- Insulated to R13
- 5 Year Warranty on paint coatings
- Available in SeaCool™ Thermal coatings for reduced heat loading



External Length	2,438 mm	8' - 0"
External Width	1,968 mm	6' - 5.5"
External Height	2,438 mm	8' - 0"
Internal Length	2,299 mm	7' - 6.5"
Internal Width	1,882 mm	6' - 2.06"
Internal Height	2,262 mm	7' - 5.81"
Door Opening Width	1,874 mm	6' - 1.75 "
Door Opening Height	2,164 mm	7 - 1.187"
Maximum Gross Weight	6,759 kg	14,900 lbs
Tare Weight	1,180 kg	2,600 lbs
Payload Weight	5,579 kg	12,300 lbs
Internal Volume	9.79 cu. mt	345.6 cu.ft.
Fork Pocket-Height	115 mm	4' - 0.53"
Fork Pocket-Width	356 mm	1' - 2.02"
Fork Pocket-Centers	902 mm	2' - 11.5"

DURABLE VERSATILE AFFORDABLE